HOOKER BOATS		5		6	6	6				5		6	6	6	Not a			5		6	6	6	
	5	5	6	5 0	7	7 5			5	5	6	5 0	7	7 5	8		5	5	6	5 0	7	7 5	۶
Hardware	3	5	0	U	,	5	0	Plumbing	5	Э	В	U	,	5	0	Fiberglass components	э	3	6	U	,	3	·
Bow roller stainless	•	•	•	•	•	•	•	Fresh water tank	0	0	0	0	0	0	0	Transom door	‡	‡	‡	•	•	•	
Tow eyes stainless	•	•	•	•	•	•	•	Live bait tank plumbed	0	0	0	•	•	•	•	Bow sprite	•	•	•	•	•	•	
Bollard stainless	•	•	•	•	•	•	•	Deck wash plumbed	0	0	0	•	•	•	•	Footrest	‡	‡	‡	•	•	‡	
SSs steel fold up cleats	0	0	0	0	•	•	•	Canopies								Windscreens/ hatches							
Standard horn cleats	•	•	•	•	‡	‡	‡	F/glass hardtop with s/s	‡	‡	‡	‡	‡	‡	‡	Clear perspex screen	•	•	•	•	•	•	
SS rod holders standard	•	•	•	•	•	•	•	Extension to hardtop s/s	‡	‡	‡	‡	‡	‡	‡	Structural							
Drink holders	0	0	0	0	•	•	•	Stainless targa top	0	0	0	0	•	0	•	Biaxial 887 wovings	•	•	•	•	•	•	
Hand rails ss in combings	•	•	•	•	•	‡	‡	Alloy t-top - Relaxn kit	0	0	0	0	‡	‡	‡	316 Stainless fasteners	•	•	•	•	•	•	
Storage/ esky								Alloy powdercoated	0	0	0	0	0	•	0	Foam Filled closed cell	•	•	•	•	•	•	
Fwd storage compartment	•	•	•	•	•	•	•	Stainless Steel								No timber	•	•	•	•	•	•	
Forward storage insulated	0	0	0	•	•	•	•	Boarding ladder	0	0	0	•	•	•	•	10yr structural hull warranty (1 Year commercial)							
Anchor well single	•	•	•	•	•	•	•	Stainless steel bow rail	•	•	•	0	•	0	•	Specifications							
Anchor well double hatch	‡	‡	‡	‡	•	‡	•	SS grab rail over screen	•	•	•	•	‡	‡	‡	Length over all (mtrs)	5.2	5.75	6.2	6.6	6.7	6.72	7
Under floor kill pen	•	•	•	•	•	•	•	Stainless steel hand rails	•	•	•	•	•	•	•	Length on GAL trailer (mtrs)	6.5	7	7	8.5	8.5	8.5	9
Storage under helm seat	0	0	0	•	0	•	0	Fuel								Beam (mtrs)	1.85	2.15	1.85	2.3	2.4	2.4	2
Insulated helm seat	•	•	•	0	•	0	•	Fuel sender unit	•	•	•	•	•	•	•	Draft (mm)	300	300	300	300	400	400	4
Tackle draw	0	0	0	•	0	•	0	Seating								Weight (Hull dry weight) KG	700	800	800	1000	1200	1200	13
Electrical								Dual signature seating	0	0	0	0	0	•	0	Deadrise (degrees)	22	19	22	19	22	22	2
Switch panels	•	•	•	•	•	•	•	Helm seat -Ins/Cushion	•	•	•	0	•	0	•	Fuel (liters)	200	200	280	300	350	400	5
Single bilge and float	•	•	•	•	‡	‡	‡	Swing over backrest	0	0	0	0	0	‡	•	HP rating single engine	115	150	150	225	250	250	3
Dual bilge and float	0	0	0	0	•	•	•	Fiberglass components								HP rating twin engines				280		300	4
LED navigation lights	•	•	•	•	•	•	•	recess for fire ext/ epirb	0	0	0	0	0	•	0	Max motor weight (kg) single en	176	230	230	280	280	280	5
Battery tray	•	•	•	•	•	•	•	SS removable baitboard	0	0	0	•	•	•	•	Max. motor weight (kg) twin eng	ines			490		490	5
Master switch	0	0	0	•	•	•	•	Side Pockets	•	•	•	•	•	•	•	Max KW single engine	86	112	112	168	186	186	2
Floodlight	0	0	0	0	•	•	•	Side pockets-LED light	0	0	0	•	•	•	•	Max People weight (kg)	375	450	450	540	540	540	7
Steering								Feet recess - side pockets	•	•	•	•	•	•	•	Max carry weight (kg)	750	1000	1000	1100	1300	1300	15
Hydraulic steering	•	•	•	•	•	•	•	Console access door	‡	‡	‡	•	‡	•	‡	Freeboard - (mm)	620	680	620	650	700	700	7
weights are approx and can vary			lengt	ths ar	nd we	ight c	an var	y due to different models of trailers o	and mo	tors u	sed.					Height on trailer (mtrs)	2.4	2.4	2.4	2.5	3	3	3
Whilst every care has heen taken t	o nrov	ide a	ccura	te inf	orma	tion, ı	veight:	s and specs can differ due to being h	and mc	de bo	ats.					Foam Filled buoyancy	STD	STD	STD	STD	STD	STD	s