

HOOKER BOATS PRO FISHERMAN FEATURES

● Standard ○ Optional ‡ Not available

| | 5 | 5 . | 5 5 | 6 | 6 5 | 6 7 5 | 8 |
|----------------------------|---|--------|--------|---|--------|-------------|---|
| Hardware | | | | | | | |
| Bow roller stainless | ● | ● | ● | ● | ● | ● | ● |
| Tow eyes stainless | ● | ● | ● | ● | ● | ● | ● |
| Bollard stainless | ● | ● | ● | ● | ● | ● | ● |
| SSs steel fold up cleats | ○ | ○ | ○ | ○ | ○ | ● | ● |
| Standard horn cleats | ● | ● | ● | ● | ● | ‡ | ‡ |
| SS rod holders standard | ● | ● | ● | ● | ● | ● | ● |
| Drink holders | ○ | ○ | ○ | ○ | ○ | ● | ● |
| Hand rails ss in combings | ● | ● | ● | ● | ● | ‡ | ‡ |
| Storage/ esky | | | | | | | |
| Fwd storage compartment | ● | ● | ● | ● | ● | ● | ● |
| Forward storage insulated | ○ | ○ | ○ | ○ | ● | ● | ● |
| Anchor well single | ● | ● | ● | ● | ● | ● | ● |
| Anchor well double hatch | ‡ | ‡ | ‡ | ‡ | ‡ | ‡ | ● |
| Under floor kill pen | ● | ● | ● | ● | ● | ● | ● |
| Storage under helm seat | ○ | ○ | ○ | ○ | ● | ● | ● |
| Insulated helm seat | ● | ● | ● | ○ | ○ | ○ | ○ |
| Tackle draw | ○ | ○ | ○ | ○ | ● | ● | ● |
| Electrical | | | | | | | |
| Switch panels | ● | ● | ● | ● | ● | ● | ● |
| Single bilge and float | ● | ● | ● | ● | ● | ‡ | ‡ |
| Dual bilge and float | ○ | ○ | ○ | ○ | ○ | ● | ● |
| LED navigation lights | ● | ● | ● | ● | ● | ● | ● |
| Battery tray | ● | ● | ● | ● | ● | ● | ● |
| Master switch | ○ | ○ | ○ | ○ | ● | ● | ● |
| Floodlight | ○ | ○ | ○ | ○ | ○ | ● | ● |
| Steering | | | | | | | |
| Hydraulic steering | ● | ● | ● | ● | ● | ● | ● |
| Plumbing | | | | | | | |
| Fresh water tank | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| Live bait tank plumbed | ○ | ○ | ○ | ○ | ● | ● | ● |
| Deck wash plumbed | ○ | ○ | ○ | ○ | ● | ● | ● |
| Canopies | | | | | | | |
| F/glass hardtop with s/s | ‡ | ‡ | ‡ | ‡ | ‡ | ‡ | ‡ |
| Extension to hardtop s/s | ‡ | ‡ | ‡ | ‡ | ‡ | ‡ | ‡ |
| Stainless targa top | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| Alloy t-top - Relaxn kit | ○ | ○ | ○ | ○ | ○ | ‡ | ‡ |
| Alloy powdercoated | ○ | ○ | ○ | ○ | ○ | ● | ● |
| Stainless Steel | | | | | | | |
| Boarding ladder | ○ | ○ | ○ | ○ | ● | ● | ● |
| Stainless steel bow rail | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| SS grab rail over screen | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| Stainless steel hand rails | ● | ● | ● | ● | ● | ● | ● |
| Fuel | | | | | | | |

| | | | | | | |
|---|------|------|------|------|------|------|
| Fuel sender unit | ● | ● | ● | ● | ● | ● |
| Seating | | | | | | |
| Dual signature seating | ○ | ○ | ○ | ○ | ● | ● |
| Helm seat -Ins/Cushion | ● | ● | ● | ○ | ○ | ○ |
| Swing over backrest | ○ | ○ | ○ | ○ | ‡ | ● |
| Fiberglass components | | | | | | |
| recess for fire ext/ epirb | ○ | ○ | ○ | ○ | ● | ● |
| SS removable baitboard | ○ | ○ | ○ | ● | ● | ● |
| Side Pockets | ● | ● | ● | ● | ● | ● |
| Side pockets-LED light | ○ | ○ | ○ | ● | ● | ● |
| Feet recess - side pockets | ● | ● | ● | ● | ● | ● |
| Console access door | ‡ | ‡ | ‡ | ● | ● | ● |
| Fiberglass components | | | | | | |
| Transom door | ‡ | ‡ | ‡ | ● | ● | ● |
| Bow sprite | ● | ● | ● | ● | ● | ● |
| Footrest | ‡ | ‡ | ‡ | ‡ | ○ | ○ |
| Windscreens/ hatches | | | | | | |
| Clear perspex screen | ● | ● | ● | ● | ● | ● |
| Structural | | | | | | |
| Biaxial 887 wovings | ● | ● | ● | ● | ● | ● |
| 316 Stainless fasteners | ● | ● | ● | ● | ● | ● |
| Foam Filled closed cell | ● | ● | ● | ● | ● | ● |
| No timber | ● | ● | ● | ● | ● | ● |
| 10yr structural hull warranty (1 Year commercial) | | | | | | |
| Specifications | | | | | | |
| Length over all (mtrs) | 5.2 | 5.75 | 6.3 | 6.6 | 6.75 | 7.8 |
| Length on GAL trailer (mtrs) | 6.5 | 7 | 7 | 8.5 | 8.5 | 9.5 |
| Beam (mtrs) | 1.85 | 2.15 | 1.85 | 2.3 | 2.4 | 2.4 |
| Draft (mm) | 300 | 300 | 300 | 300 | 400 | 400 |
| Weight (Hull dry weight) KG | 700 | 750 | 750 | 900 | 1200 | 1350 |
| Deadrise (degrees) | 22 | 19 | 22 | 19 | 22 | 24 |
| Fuel (liters) | 200 | 200 | 280 | 300 | 400 | 500 |
| HP rating single engine | 115 | 150 | 150 | 215 | 250 | 300 |
| HP rating twin engines | | | | 215 | 250 | 300 |
| Max motor weight (kg) single eng | 225 | 275 | 275 | 295 | 295 | 395 |
| Max. motor weight (kg) twin engines | | | | 590 | 590 | 790 |
| Max KW single engine | 86 | 112 | 112 | 160 | 186 | 224 |
| Max People weight (kg) | 450 | 450 | 450 | 450 | 540 | 720 |
| Max carry weight (kg) | 900 | 1000 | 1000 | 1300 | 1400 | 1500 |
| Freeboard - (mm) | 620 | 680 | 620 | 650 | 700 | 700 |
| Height on trailer (mtrs) | 2.4 | 2.4 | 2.4 | 2.5 | 3 | 3.1 |
| Foam Filled buoyancy | STD | STD | STD | STD | STD | STD |
| | | | | | | |

weights are approx and can vary - lengths and weight can vary due to different models of trailers and motors used.

Whilst every care has been taken to provide accurate information, weights and specs can differ due to being hand made boats.

Motor weights include rigging, battery and accessories