

HOOKER BOATS CABIN MODELS FEATURES

● Standard ○ Optional ‡ Not available

	575C	675SC	675WRC	8WRC	8SC
Hardware					
Bow roller stainless	●	●	●	●	●
U-bolts and tow eyes stainless	●	●	●	●	●
Bollard stainless	●	●	●	●	●
Stainless steel fold up cleats	○	●	●	●	●
Standard horn cleats	●	‡	‡	‡	‡
Stainless rod holders standard	●	●	●	●	●
Hand rails ss in combings	●	‡	‡	‡	‡
Storage/ esky					
Shelves in cabin	●	●	●	●	●
Storage under bunks	●	●	●	●	●
Anchor well single	●	●	●	●	●
Anchor well double hatch	‡	‡	‡	●	●
Under floor kill pen	●	●	●	●	●
Storage under helm seat	○	○	●	●	○
Insulated helm seat	○	○	●	●	○
Tackle draw	○	○	○	○	●
Electrical					
Switch panels	●	●	●	●	●
Single bilge and float switch	●	‡	‡	‡	‡
Dual bilge and float switch	○	●	●	●	●
LED navigation lights	●	●	●	●	●
Battery tray	●	●	●	●	●
Master switch for batteries	○	●	●	●	●
Floodlight	○	○	○	○	○
Steering					
Hydraulic steering	●	●	●	●	●
Plumbing					
Fresh water tank	○	○	○	○	○
Live bait tank plumbed	○	○	○	○	○
Deck wash plumbed	○	○	○	●	●
Canopies					
Fibreglass hardtop	‡	○	○	○	○
Extension to hardtop s/s	‡	○	○	○	○
Stainless canopy	○	○	○	○	○
Alloy canopy powdercoated	○	○	○	○	○
Stainless Steel					
Boarding ladder	●	●	●	●	●
Stainless steel bow rail	●	●	●	●	●
Fuel					
Fuel sender unit	●	●	●	●	●
Seating					
Bucket pedestals	●	●	●	●	●
Insulated helm seat boxes	○	○	●	●	○

Fiberglass components					
recess for fire ext and epirb	○	●	●	●	●
Stainless removable baitboard	○	○	○	○	○
Side Pockets	●	●	●	●	●
Side pockets with LED light	○	●	●	●	●
Feet recess - side pockets	●	●	●	●	●
Console access door	‡	‡	‡	‡	‡
Transom door	‡	●	●	●	●
Bow sprite	●	●	●	●	●
Footrest	‡	●	●	●	●
Windscreens/ hatches					
Polycarb windscreen	●	●	●	●	●
Toughened glass windscreen	○	●	●	●	●
Structural					
Biaxial 887 wovings	●	●	●	●	●
316 Stainless fasteners	●	●	●	●	●
Foam Filled closed cell	●	●	●	●	●
No timber	●	●	●	●	●
10Yr structural hull warranty (1 Year commercial)	●	●	●	●	●
Specifications					
Length over all (mtrs)	5.75	6.75	6.75	7.8	7.8
Length on trailer (mtrs)	7	8	8	9	9
Beam (mtrs)	2.15	2.4	2.4	2.4	2.4
Draft (mm)	300	300	300	400	400
Weight (Hull dry weight) KG	800	1200	1200	1350	1350
Deadrise (degrees)	19	22	22	24	24
Fuel (liters)	150	400	400	500	500
HP rating single engine	150	250	250	300	300
HP rating twin engines		250	250	300	300
Max motor weight (kg) single engine	275	295	295	395	395
Max. motor weight (kg) twin engines		590	590	790	790
Max KW single engine	112	186	186	224	224
Max People weight (kg)	450	540	540	720	720
Max carry weight (kg)	1000	1300	1300	1500	1500
Freeboard - (mm)	680	700	700	700	700
Height on trailer (mtrs)	2.4	3	3	3.1	3.1
Foam Filled buoyancy	STD	STD	STD		STD

weights are approx and can vary

lengths & weight can vary due to different models of trailers and motors used.

Whilst every care has been taken to provide accurate information, weights and specs can differ due to being hand made boats.

Motor weights include rigging, battery and accessories